



Color Copy coated glossy has a coating specially adapted to digital colour laser printing with a unique gloss effect. It is especially suitable for leaflets, annual reports and brochures.



Technical Data: COLOR COPY COATED GLOSSY

			135	170	200	250	300	350
Basis weight	g/m ²	ISO 536	135 ± 3.0	170 ± 4.0	200 ± 6.0	250 ± 8.0	300 ± 10.0	350 ± 12.0
Caliper	µm	ISO 534	107 ± 4	136 ± 6	162 ± 7	213 ± 9	260 ± 11	312 ± 14
Smoothness Bekk	sec	ISO 5627	1000 ± 300	500 ± 150	400 ± 120	250 ± 75	180 ± 60	180 ± 60
Opacity	%	ISO 2471	95.0 ± 1	97.0 ± 1	99.0 ± 1	100.0	100.0	100.0
Moisture abs.	%	ISO 287	4.8 ± .6	4.8 ± .6	4.8 ± .6	4.8 ± .6	4.8 ± .6	4.8 ± .6
Brightness UV	%	ISO 2470	103.0 ± 2.0	103.0 ± 2.0	103.0 ± 2.0	103.0 ± 2.0	103.0 ± 2.0	103.0 ± 2.0
CIE Whiteness	%	ISO 11475	139 ± 2.5	139 ± 2.5	139 ± 2.5	139 ± 2.5	139 ± 2.5	139 ± 2.5
Gloss 75°	TS %	TAPPI T 480	75 ± 4	75 ± 4	75 ± 4	75 ± 4	75 ± 4	75 ± 4

Product meets EN 12281, requirements for copy paper for dry toner imaging processes and ISO 9706, requirements for permanence for paper. Production processes certified according to ISO 9001. Standard measurement uncertainty between laboratories is not incorporated.

SIGNIFICANCE OF VALUES: 2 SIGMA

This specification is valid for one year after issue or good till cancelled.